


ergo *Wind*



Wind Turbine
EW 20

**WE CANNOT
SOLVE OUR PROBLEMS
WITH THE SAME LEVEL OF THINKING
THAT CREATED THEM.**

Albert Einstein

Ergo Wind srl

Ergo Wind is leader in offering low environmental impact energy systems for the small wind market. Right from its founding, the company has always invested in research and development of new technologies, cooperating in partnership with the highly qualified team of TCS Energie, a successful company with thirty years of experience in the field of renewable energy sector. Ergo Wind core business is represented by small wind turbines from 20 kW to 60 kW power, designed and manufactured in our factory located in Pesaro, with the precious partnership of Università Politecnica delle Marche and other influential Italian and European companies.

Our strategic technical choices rank Ergo Wind small turbines among small wind products with the best value for money on the market and guarantee maximum reliability, efficiency and durable functioning over time. In order to ensure full transparency, Ergo Wind allows to visit its factory and supplies monitoring system that allows the access to statistical data of your wind turbine.

Our qualified staff is also able to offer technical support and assistance for siting processes and due diligence and our after sales and maintenance centers are located throughout the country.

Ergo Wind turbines are designed and manufactured according to IEC 61400-2 regulation. Every mechanical and electromechanical component is realized by qualified European and Italian companies, in order to guarantee maximum reliability, efficiency and durable functioning over time.

1

The lowerable/raisable hydraulic tower allows to reduce drastically maintenance costs.



2

No Inverter.

**"IF IT ISN'T THERE,
IT CAN'T BREAK."**

Henry Ford



3

Our investors can count on the access to objective and demonstrable production data.



TRUSTWORTHINESS

STALL REGULATED SYSTEM



When the wind speed increases and the turbine is at the top of speed, the blades, specifically designed with this technology, limit automatically and progressively the power captured by the wind. This allows the turbine to work constantly even with high wind speed, without the need for yaw system to limit the power, avoiding overload and taking advantage for the durability of the components.



LOW INSTALLATION AND MAINTENANCE COSTS

HYDRAULIC TOWER

Our wind turbines have a tower provided with an hydraulic system for the lifting and lowering, in order to obtain economic advantages both during installation and maintenance, as all the operations are carried out in the ground and not in altitude. The time required to lower/raise the turbine are approximately 20 minutes, without the utilization of cranes, platforms or operators trained to work in high altitude.



YAW SYSTEM

The yaw system is composed by a slewing drive able to guarantee high rotational coupling and rotor locking during operation. The hydraulic motorization gives profits in terms of trustworthiness, performance, lightness, obstacle and maintenance. The pump of the slewing drive is located inside the technical compartment on the ground. Its special sensors allow to optimize the wind heading thanks to accurate corrections.



HUB

The hub is made by a single block in aluminium alloy. Inside there is a cast iron bush GS400 for the coupling of turbine shaft. Each hub is x-rayed, connecting the benefit of the lightness and trustworthiness.



REDUNDANT SAFETY

The safety of the wind turbine is guaranteed thanks to the adoption of redundant braking systems. The negative electromechanical braking system acts promptly and fastens the rotor in absence of any power source. The aerodynamic brake, installed on each blade, is automated and completely mechanical and acts by limiting the improbable overspeed of the rotor. Furthermore, this system keeps the appendixes anchored to the hub through a steel cable inside the blade.



DIRECT CONNECTION TO THE POWER GRID WITHOUT INVERTER

Our wind turbines are connected directly to grid power without inverter (through the interface system required by the electricity service provider), increasing the global efficiency of the system and deleting the odds of damages in electronic devices.

**100% .
wind
energy!**



TECHNICAL FEATURES

Wind Turbine

Configuration	Upwind
Rated power (kW)	20
Rated generator speed (Rpm)	78
Turbine International Standard IEC 61400-2	III
Rated wind speed (m/s)	10
Maximum wind speed (m/s)	52,5
Cut off wind speed (m/s)	25
Total weight (Nacelle + Rotor) (kg)	1100

Rotor

Rotor diameter (m)	10,8
Swept area (m ²)	92
Blade length (m)	5,1
Blade material	Reinforced fiber glass
Power regulation	Aerodynamic stall

Wind Turbine

Tipology	Asynchronous
Configuration	Three phases, 4 poles, 400Vac
Rated power (kW)	20
Multiplier	Two stages parallel axes

Inverter	No
-----------------	-----------

Braking systems and safety	Negative brake system on the turbine, aerodynamic brake and yaw system
-----------------------------------	--

Control systems

Control system	PLC + Touch Screen
Monitoring system	Web app, daily/weekly/monthly/annual report


Towers

Hub heights available (m)	20
Tower typology	Raisable/lowerable tower

Warranty	2 years with possibility of extension
-----------------	---------------------------------------




EW 20 - ELECTRIC POWER (kW-m/s)



ANNUAL PRODUCTION OF ELECTRICITY AEP (kWh/year)

Wind speed (m/s)	AEP (kWh/year)
3,0	17023
3,5	24075
4,0	32100
4,5	40611
5,0	49609
5,5	58364
6,0	66632
6,5	74414
7,0	81709
7,5	87545
8,0	93382



Ergo Wind reserves the right to alter product specifications without prior notice.





Ergo Wind srl

Strada degli Olmi, 18
61121 Pesaro PU Italy
tel. +39 0721 23072
info@ergowind.it
www.ergowind.it